

GENERAL
PURPOSE
**GLASS
CHILLER
SERIES**

SKOPE STANDARD RANGE



**Specifically designed
to support efficient
bar service.**



This remote Glass Chiller supports efficient bar service by quickly chilling glasses straight from the dishwasher ensuring glasses are constantly cold.

Generic Specifications

- Operating temperature +1°C to +4°C in 40°C ambient
- Electronic controller with digital temperature display with on/off switch and neon power indicator
- Exterior: stainless steel (excluding galvanised steel top and base)
- Interior: stainless steel
- Easy plug-in 10 Amp power supply (230-240V, 50Hz), via mains flex
- Self-closing glass door with double glazed toughened single low/e argon filled safety glass
- Reversible door to suit your space
- Left hand side mounted service compartment
- Three shelf runners, to hold w14" x d17" or w14" x d14" glass racks (glass racks not included)
- Full length, ergonomic door handle
- Insulation: 50mm thick, high density cyclo-isopentane polyurethane foam (CFC, HCFC & HFC free)
- Adjustable legs as standard, also suitable for plinth mounting

Remote Specifications

- Plumbing required for drainage
- Thermostatic expansion valve fitted as standard (to suit R134a or 404A, please specify when ordering)
- See Remote Refrigeration System Specifications on page 108 for more information



GC110r

Model	Weight (kg)	Integral/Remote	Chiller/Freezer
GC110r	55	Remote	Chiller
	External (mm)	Internal (mm)	
Height*	725	660	Gross Volume 110 litres
Width	750	370	Total Shelf Area n/a
Depth	600	455	Floor Area 0.45m ²
			Top Opening w480 x d455mm

- Remote refrigeration duty 450 Watts at -5°C SST

GC110r
1 DOOR